



## Memmert Water Baths 'WTB' series

Memmert Water Bath WTB series are unparalleled in terms of precision safety and comfort. Memmert is known for excellent operating concepts - the new WTB water baths are just more proof of this. The touchscreen impresses with its intuitive and convenient menu navigation. A particular highlight: Thanks to the personalisable remote viewing through the CustomView, you always have an eye on the important information.

### Standard Equipment

**Interior:** Deep-drawn stainless steel tray (stainless steel W.St. 1-4301), heating mounted from the outside, without corners and edges for easy cleaning incl. central drain (no disturbing installations)

**Housing:** Textured stainless steel (material 1.4016)

**Display:** Intuitive 3.5" colour graphic display with touch screen

**Connection:** mains cable with plug (German type)

**Installation:** 4 feet

Stainless steel Gable cover provided as standard

### Accessories

1. Stainless steel flat cover with openings and rings
2. Shelf reversible for 2 heights (30 or 60 mm)
3. Shaking device with frequency 35-160 strokes per minute

### Salient Features

- Stainless steel interior and exterior
- Electronic PID controller
- Multiple over temperature protection
- Heating on bottom side
- Voltage 230 V, 50/60 Hz

### Options


- Voltage 115V, 50/60Hz
- Works calibration certificate at +37°C

# Memmert Water Baths 'WTB' series (7.5 to 51 litres)

Model sizes/Description			6	11	15	24	35	50
Stainless steel interior	Contents	approx. l	7.5	10	17.1	23.1	37.5	51
	Length	(A) mm	277	267	482	472	602	592
	Width	(B) mm	217	207	277	267	482	472
	Height	(C) mm	150	200	150	200	150	200
Textured stainless steel exterior	Width	(D) mm	349		554		679	
	Height (with flat cover)	(E1) mm	245	295	245	295	245	295
	Height (with gable cover)	(E2) mm	328	378	328	378	328	378
	Depth	(F) mm	289		349		554	
Temperature	Setting accuracy	°C	0.1					
	Working temperature range	°C	at least 5 above ambient to +100 (with cover, depending on ambient pressure)					
	Setting temperature range	°C	+10 to +100					
Further data	Electrical load at 230/115 V, 50/60 Hz	approx. W	1000		1420		2800	
Packing data	Net weight (with one cover option)	approx. kg	6	7	9	10	14	16
	Gross weight (in carton)	approx. kg	10	12	14	16	20	23
	Length	approx. mm	570		670		910	
	Width	approx. mm	450		530		610	
	Height	approx. mm	420	380	400	460	400	460
<b>Order No. Waterbaths</b>			<b>WTB6</b>	<b>WTB11</b>	<b>WTB15</b>	<b>WTB24</b>	<b>WTB35</b>	<b>WTB50</b>

CE ENEC


Gable cover



Flat cover



Shelf reversible for 2 heights



Test tube rack

product range

- Ovens
- Incubators
- Sterilisers
- Vaccum Ovens
- Peltier Cooled Incubators
- CO2 Incubators
- Constant Climate Chambers
- Humidity Chambers
- Stability Test Chambers
- Water Baths
- Clean Room Drying Ovens
- Pass Through Ovens

[www.memmert.com](http://www.memmert.com)

## Head Office:

### Memmert GmbH + Co.KG

P.O. Box 1720, D-91107 Schwabach, Germany  
 Tel : +49 9122 925-0 Fax : +49 9122 14585  
 E-Mail : sales@memmert.com

## Local Sales & Support Office:

### Memmert India Laboratory Equipment Private Limited

Manas, 64 Lokmanya Colony, Near Utsav Hall, Paud Road  
 Kothrud, Pune 411038, Maharashtra, India  
 Mobile : +91 8390786810 / +91 7720044027 | E-mail : sales.india@memmert.com